TC-14K-2 TRAILER CONVEYOR
Technical Specifications & Dealer Pricing

DIMENSIONS & WEIGHT:

Length Overall	36'-0"	11,00 m
Width Overall	8'-0"	2,44 m
Deck Height	30"	0,76 m
Hitch Type	Holland Lunette eye	2 5/8" 67 mm dia.
Hitch Height	28"	0,71 m
Tongue Weight – Loaded	1,250 to 1,350lbs.	568 to 614 kg
Weight w/o Options	5,000 lbs.	2,273 kg
Carrying Capacity	10,000 lbs.	4,540 kg
GVWR – Max	14,000 lbs.	6,350 kg
Suspension / Axles	(4) Leaf springs, tandem (double) axle set	
Gross Axle Capacity	7,000 lbs/each x 2	3,175 kg / each x 2
Spindle Lubrication	"EZ" Lube / "Bearing Buddies" 4	
Wheels / Tires Brake	@ 3,500 lbs. / 1,587 kg	
Light Set	12-Volt D.C.	

CONVEYOR: with Stainless Steel Frame

Length	20'	6,1 m
Width	5'-2"	1,57 m
Capacity	9,000 lbs.	4,080 kg
Conveyor Belting	**Heavy Duty** galvanized flat wire mesh	
Electric Motor	One electric drive shaft motor	
Sides and Gate	SS Sides, Steel Gate, Removable, 12" / 31 cm high	

ACCESSORIES

Winch	12 Volt Electric	
Winch Pull	9,500 lbs	1,590 kg
Swivel Jacks, 2 Mechanical w Drop Legs	8,000 lbs.	3,628 kg
Safety Chains with Safety Clasp Hooks	2 HD @ 36" long	91 cm long
Electric Connector	6-prong round, standard	
Breakaway Electric Control	Standard kit with charger, included	
Trailer Lighting	Conforms to DOT Code. Suitable for water launch	

Base Coat – Epoxy Primer Top Coat – Urethane – Black.

TC-14K-2 TRAILER CONVEYOR
Technical Specifications & Dealer Pricing

Tires – 4 – ST235R16 LRE on 8 bolt 16" white spoke steel wheels.

Holland Tow Ring for Pintle Hook with 5 adjustable height positions bolted to a face plate with 4 grade 8 bolts 5/8" with hard Washers and Stover grade 8 lock nuts.

L.E.D. Sealed marker and tail lights wired to DOT specifications to one terminal block at front of trailer. The rear lights mounted in Recessed, vibration resistant housings in a portable light bar. Separate power cord provided to plug light bar into trailer.

No outside exposed connections. All connections are crimped, soldered, heat shrink sealed and loomed into corrugated, spiral tubing.

Trailer is designed and built to DOT rules and regulations and is Ministry of Transportation of Ontario (MTO) certified. Customer to verify trailer is suitable for and meets local use requirements.

TC-14K-2 Dealer Pricing USD 44,980.00

Options:

Spare Tire, Rim and mounting bracket	USD 690.00
Heavy Duty Stainless Steel Belting – Replaces Heavy Duty Galvanized belting	USD 2,980.00
Full Solid UHMW PE floor under top belting Replaces Strips of UHMW PE (Helpful for containing Duckweed and Trash)	USD 3,980.00
Chain and Binders Tie Down Kit	USD 980.00

NOTES:

The TC-14K-2 Trailer Conveyor is designated for use with Harvester H6 Models H5 Models, AQS-200 Skimmer Boat, and TBO-4K-II Aquatic Transporter.
Please note that for sea container shipping our pricing does not include crane loading into container, but crane loading assistance is available upon customer request free of charge.
Your shipping supplier will need to include the "blocking, bracing, and packaging" of your machine in the container and the materials required to do so.
Due to shipping regulations all equipment is sold and shipped without any fluids or batteries.
Due to Aquamarine's ongoing efforts to improve its products, specifications are subject to change without notice.